REPAIR STAND COMPARISON CHART

Warranty 3 year limited

	PRO E LIFT	PRO AIR LIFT	PRO MECHANIC HD	PRO MECHANIC	SPRINT	PRO ULTRALIGHT	SPORT MECHANIC 2.0
Clamp Style	Speed Ratchet + Spinner Knob	Speed Ratchet + Spinner Knob	Speed Ratchet + Spinner Knob	Speed Ratchet + Spinner Knob	Dropout	Slide Lock + Spinner Knob	Weighted Spinner
Fittings	N/A	Metal Quick Release					Threaded Z-Knob
Working Footprint [Tripod Diameter]	27.75" x 28.5" 70.5 cm x 72.4 cm	56.25" 142.9 cm	55.5" 141cm	54" 137.2 cm	45.5" 115.6 cm	54" 137.2 cm	54" 137.2 cm
Folded Dimensions	27.75" x 28.5" x 39.25" 70.5 cm x 72.4 cm x 99.7 cm	6.9" x 8.6" x 45.4" 17.5 cm x 21.8 cm x 115.3 cm	6.8" x 8.6" x 45.4" 17.3 cm x 21.8 cm x 115.3 cm	5" x 8" x 45" 12.7 cm x 20.3 cm x 114.3 cm	5" x 7.5" x 30" 12.7 cm x 19.1 cm x 76.2 cm	5.125" x 6.53" x 37.5" 13.0 cm x 16.6 cm x 95.3 cm	5.125" x 6.53" x 44.7" 13.0 cm x 16.6 cm x 113.5 cm
Product Weight	54 lbs. / 24.5 kg	17.9 lbs. / 8.1 kg	16.8 lbs. / 7.6 kg	12.25 lbs. / 5.6kg	12.0 lbs. / 5.4 kg	10.8 lbs. / 4.9 kg	12.4 lbs. / 5.6 kg
Max Capacity	100 lbs. / 45.4 kg	100 lbs. / 45.4 kg	100 lbs. / 45.4 kg	85 lbs. / 38.6 kg	85 lbs. / 38.6 kg	85 lbs. / 38.6 kg	85 lbs. / 38.6 kg
Adjustable Clamp Arm Height Range	35.75" - 73" 90.8–185.4 cm	42.5" - 66.5" 108.0–168.9 cm	42" - 67" 106.7–170.2 cm	42" - 67" 106.7–170.2 cm	30" - 48" 76.2–121.9 cm	34" - 57.5" 86.4–146.1 cm	41" - 66" 104.1–167.6 cm
Clamp Jaw Opening	2.6" / 6.6 cm	2.6" / 6.6 cm	2.6" / 6.6 cm	2.6" / 6.6 cm	QR: 100/130/135mm T/A: 12x100/142/148, 15x100/110mm	1.78" / 4.5 cm	1.9" / 4.8cm
Material	Steel	6063 Aluminum					Aluminum/Steel
Travel Bag	Not Available	Optional	Optional	Optional	Optional	Included	Optional
Tool Tray	Optional	Optional	Optional	Optional	Optional	Optional	Included
Ideal For Bikes	E-bikes/Cargo/MTB/ Road/Gravel ≤ 100 lbs. / 45.4 kg	E-bikes/Cargo/MTB/ Road/Gravel ≤100 lbs. / 45.4 kg	MTB/Road/Gravel ≤75 lbs. / 34 kg	MTB/Road/Gravel ≤45 lbs. / 20.4 kg	MTB/Road/Gravel TT/Tri/Aero Posts ≤45 lbs. / 20.4 kg	MTB/Road/Gravel ≤35 lbs. / 15.9 kg	MTB/Road/Gravel ≤45 lbs. / 20.4 kg
WEIGHT CAPACITY							
CLAMP FEATURES							
STIFFNESS							
PORTABILITY							